

PRODUCT FEATURES

- Electrically welded, unthreaded thin walled mild steel tube
- Manufactured from Pre Galvanised cold rolled coil
- Supplied in 10' (3 m) lengths without couplers
- Connected using clamp-type fittings (available separately)
- Non Underwriters Laboratory UL797
- American National Standard ANSI C80.3
- Designed to protect & route electrical wiring
- Hot dipped galvanised finish and alternative lengths are available on request



SPECIFICATIONS

- Outside Diameter Tolerance

Nom Trade Size up to 2"	+ 0.005" (+ 0.13mm)
Nom Trade Size 2½ "	+ 0.010" (+ 0.25mm)
Nom Trade Size 3"	+ 0.015" (+ 0.38mm)
Nom Trade Size 3½ & 4"	+ 0.020" (+ 0.51mm)

- Length Tolerance + 0.125" (+ 6.35mm)
- Height of internal weld bead is 0.3mm max
- Pre Galv zinc thickness 12µ total.
- Both ends plain finish (no threads)
- Couplers not included

ELECTRICAL METALLIC TUBING (PRE GALVANISED UNTHREADED STEEL CONDUIT)

	Product Code	Trade Size	Metric size	Outside Diameter	Length (customizable)	Qty. Per Bundle	
		inch	mm	mm	mm	ft	Pcs.
1/2" EMT CONDUIT TUBE	C16EMTTUBE	½"	16	17.93	3050	10	200
3/4" EMT CONDUIT TUBE	C20EMTTUBE	¾"	21	23.42	3050	10	200
1" EMT CONDUIT TUBE	C27EMTTUBE	1"	27	29.54	3050	10	100
1- ¼ EMT CONDUIT TUBE	C35EMTTUBE	1-¼"	35	38.35	3050	10	5
1- ½ " EMT CONDUIT TUBE	C41EMTTUBE	1-½ "	41	44.2	3050	10	5
2" EMT CONDUIT TUBE	C53EMTTUBE	2"	53	55.8	3050	10	5